

	Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)	M (μ)	S (μ)	Subdial position	Day/Date/Month	Power Engine	Battery	Battery life (year)	
<b>Standard</b>														
Basic	2025	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	1.30	850	450					SR626SW	3	
	2026	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	2.75	2,400	350					SR626SW	3	
	2035	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	1.60	850	400	350			●	SR626SW	3	
	2036	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	2.10	1,200	500	400			●	SR626SW	3	
	2039	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	2.30	1,700	300	300			●	SR626SW	3	
	2033	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	2.56	1,850	460	250			●	SR626SW	3	
	203A	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	3.35	2,500	400	450			●	SR626SW	3	
	Super 2035	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	1.60	850	400	350			●	SR626SW	4	
	2037	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	1.60	850	400	350			●	SR626SW	3	
	2034	6 3/4 x 8 <sup>mm</sup>	3.15	1.10	1.80	850	400	550				SR626SW	14 month	
	2015	6 3/4 x 8 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Date	●	SR626SW	3	
	2005	6 3/4 x 8 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Day Date	●	SR626SW	3	
	2115	10 1/2 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Date	●	SR626SW	3	
	2117	10 1/2 <sup>mm</sup>	4.15	2.10	2.15	1,400	400	350		Date	●	SR626SW	3	
	2105	10 1/2 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Day Date	●	SR626SW	3	
	2315	11 1/2 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Date	●	SR626SW	3	
	2317	11 1/2 <sup>mm</sup>	4.15	2.10	2.15	1,400	400	350		Date	●	SR626SW	3	
	2305	11 1/2 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Day Date	●	SR626SW	3	
	2350	11 1/2 <sup>mm</sup>	4.15	2.10	1.85	1,100	400	350		Day Date	●	SR626SW	3	
	2415	13 1/2 <sup>mm</sup>	4.35	2.30	1.95	950	500	500		Date	●	SR626SW	3	
	2417	13 1/2 <sup>mm</sup>	4.35	2.30	2.15	1,200	500	450		Date	●	SR626SW	3	
	2405	13 1/2 <sup>mm</sup>	4.35	2.30	1.95	950	500	500		Day Date	●	SR626SW	3	
Small Second	1L40	6 3/4 x 8 <sup>mm</sup>	2.93	1.35	1.60	1,200	400		6			SR621SW	3	
	1L45	6 3/4 x 8 <sup>mm</sup>	2.93	1.35	1.60	1,200	400		6			SR621SW	3	
10 Year Battery	1L60	6 3/4 x 8 <sup>mm</sup>	4.30	1.13	1.50	800	400	300				CR1616	10	
	2S60	10 1/2 <sup>mm</sup>	3.99	1.13	1.50	800	400	300		Date		CR2012	10	
	2S65	10 1/2 <sup>mm</sup>	4.22	1.36	1.50	850	350	300		Day Date		CR2012	10	
<b>Slim</b>														
Super Slim	9T22	6 3/4 x 8 <sup>mm</sup>	1.90	0.58	1.15	800	350					SR616SW	3	
	9T15	6 3/4 x 8 <sup>mm</sup>	2.33	1.01	1.08	750	330			Date		SR616SW	2	
	9T33	6 3/4 x 8 <sup>mm</sup>	1.90	0.58	1.43	800	340	290				SR616SW	2	
	9T13	6 3/4 x 8 <sup>mm</sup>	2.33	1.01	1.38	750	330	300		Date		SR616SW	2	
	9U15	10 1/2 <sup>mm</sup>	2.33	1.01	1.08	750	330			Date		SR916SW	4	
	9U13	10 1/2 <sup>mm</sup>	2.33	1.01	1.38	750	330	300		Date		SR916SW	4	
Basic Slim	GL22	6 3/4 x 8 <sup>mm</sup>	2.28	0.70	1.15	800	350					SR621SW	5	
	GL24	6 3/4 x 8 <sup>mm</sup>	2.28	0.70	1.60	1,200	400					SR621SW	5	
	GL17	6 3/4 x 8 <sup>mm</sup>	2.71	1.13	1.20	800	400			Date		SR621SW	5	
	GL32	6 3/4 x 8 <sup>mm</sup>	2.28	0.70	1.45	800	350	300			●	SR621SW	3	
	GL34	6 3/4 x 8 <sup>mm</sup>	2.28	0.70	2.16	1,500	360	300			●	SR621SW	3	
	GL12	6 3/4 x 8 <sup>mm</sup>	2.71	1.13	1.50	800	400	300		Date	●	SR621SW	3	
	GL14	6 3/4 x 8 <sup>mm</sup>	2.71	1.13	2.30	1,450	500	350		Date	●	SR621SW	3	
	GL02	6 3/4 x 8 <sup>mm</sup>	2.94	1.36	1.50	800	400	300		Day Date	●	SR621SW	3	
	GN17	8 3/4 <sup>mm</sup>	2.71	1.13	1.20	800	400			Date		SR621SW	5	
	GN12	8 3/4 <sup>mm</sup>	2.71	1.13	1.50	800	400	300		Date	●	SR621SW	3	
	GM17	10 1/2 <sup>mm</sup>	2.71	1.13	1.20	800	400			Date		SR621SW	5	
	GM12	10 1/2 <sup>mm</sup>	2.71	1.13	1.50	800	400	300		Date	●	SR621SW	3	
	GM14	10 1/2 <sup>mm</sup>	2.71	1.13	2.30	1,450	500	350		Date	●	SR621SW	3	
	GM02	10 1/2 <sup>mm</sup>	2.94	1.36	1.50	800	400	300		Day Date	●	SR621SW	3	
	Large	GR12	11 1/2 <sup>mm</sup>	2.71	1.13	1.50	800	400	300		Date	●	SR621SW	3
		GR02	11 1/2 <sup>mm</sup>	2.94	1.36	1.50	800	400	300		Day Date	●	SR621SW	3
<b>Small</b>														
	5Y20	5 1/2 x 6 3/4 <sup>mm</sup>	2.54	0.55	1.20	800	400					SR521SW	4	
	5Y26	5 1/2 x 6 3/4 <sup>mm</sup>	2.54	0.55	1.75	1,350	400					SR521SW	4	
	5Y30	5 1/2 x 6 3/4 <sup>mm</sup>	2.54	0.55	1.50	800	400	300				SR521SW	2	
	5Y36	5 1/2 x 6 3/4 <sup>mm</sup>	2.54	0.55	2.08	1,350	400	330				SR521SW	2	
<b>Multi-function</b>														
	6P28	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	6			SR621SW	3	
	6P26	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	3	Date		SR621SW	3	
	6P23	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	12, 6	Date		SR621SW	3	
	6P25	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	3, 9	Day Date		SR621SW	3	
	6P27	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	12, 6, 9	Day Date		SR621SW	3	
	6P29	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	3, 6, 9	Day Date		SR621SW	3	
	6P79	10 1/2 <sup>mm</sup>	3.45	1.60	2.20	1,520	380	300	3, 6, 9	Day Date		SR621SW	3	
	JP21	12 1/2 <sup>mm</sup>	4.30	2.47	2.10	1,250	450	400	3, 9	Day Date	●	SR621SW	3	
	JP27	12 1/2 <sup>mm</sup>	4.30	2.47	2.10	1,250	450	400	9	Day Date	●	SR621SW	3	
Moon-Phase	6P24	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300				SR621SW	3	
	6P21	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	12, 9	Day Date		SR621SW	3	
	6P20	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	3, 9	Day Date		SR621SW	3	
	6P00	10 1/2 <sup>mm</sup>	3.45	1.60	1.80	1,120	380	300	12, 3, 9	Day Date Month		SR621SW	3	
<b>Dual-Time / Long Life Battery</b>														
	JP75	12 1/2 <sup>mm</sup>	5.55	2.47	2.10	1,250	450	400	3, 6, 9	Day Date	●	SR621SW	8	
Dual-Time	JP11	12 1/2 <sup>mm</sup>	4.30	2.47	2.10	1,250	450	400	12, 6	Date	●	SR621SW	3	
	JP15	12 1/2 <sup>mm</sup>	4.30	2.47	2.10	1,250	450	400	12, 6, 9	Day Date	●	SR621SW	3	
	JP25	12 1/2 <sup>mm</sup>	4.30	2.47	2.10	1,250	450	400	3, 6, 9	Day Date	●	SR621SW	3	
<b>Chronograph</b>														
Regular	0S10	13 1/2 <sup>mm</sup>	4.13	1.28	1.90	1,200	400	300	12, 6, 9	Date	●	SR927W	5	
	0S00	13 1/2 <sup>mm</sup>	5.10	2.25	1.93	1,200	380	350	12, 6, 9	Day Date	●	SR927W	5	
	0S30	13 1/2 <sup>mm</sup>	4.13	1.28	1.90	1,200	400	300	12, 6, 9		●	SR927W	5	
	0S20	13 1/2 <sup>mm</sup>	5.10	2.25	1.93	1,200	380	350	3, 6, 9	Date	●	SR927W	5	
	0S11	13 1/2 <sup>mm</sup>	4.13	1.28	1.90	1,200	400	300	12, 6	Date	●	SR927W	5	
	0S21	13 1/2 <sup>mm</sup>	5.10	2.25	1.93	1,200	380	350	3, 9	Date	●	SR927W	5	
	0S60	13 1/2 <sup>mm</sup>	4.13	1.28	1.90	1,200	400	300	12, 6, 9	Date	●	SR927W	2	
	Large	6S10	15 <sup>mm</sup>	4.90	1.95	2.55	1,650	450	450	12, 6, 9	Date	●	SR927W	4
		6S20	15 <sup>mm</sup>	4.90	2.40	2.55	1,650	450	450	3, 6, 9	Date	●	SR927W	4
6S30		15 <sup>mm</sup>	4.90	1.95	2.55	1,650	450	450	2, 6, 10	Date	●	SR927W	4	
6S11		15 <sup>mm</sup>	4.90	1.95	2.55	1,650	450	450	12, 6	Date	●	SR927W	4	
6S21		15 <sup>mm</sup>	4.90	1.95	2.55	1,650	450	450	3, 9	Date	●	SR927W	3	
<b>Small Second Chronograph</b>														

JS15	12 1/2"	4.30	2.47	2.10	1,250	450	400	12, 6, 9	Date	●	SR621SW	3
JS16	12 1/2"	4.30	2.47	2.65	1,800	450	400	12, 6, 9	Date	●	SR621SW	3
JS10	12 1/2"	4.18	2.35	2.10	1,250	450	400	12, 6, 9		●	SR621SW	3
JS25	12 1/2"	4.30	2.47	2.10	1,250	450	400	3, 6, 9	Date	●	SR621SW	3
JS26	12 1/2"	4.30	2.47	2.65	1,800	450	400	3, 6, 9	Date	●	SR621SW	3
JS20	12 1/2"	4.18	2.35	2.10	1,250	450	400	3, 6, 9		●	SR621SW	3
JS05	12 1/2"	4.30	2.47	2.10	1,250	450	400	2, 6, 10	Date	●	SR621SW	3
JS06	12 1/2"	4.30	2.47	2.65	1,800	450	400	2, 6, 10	Date	●	SR621SW	3
JS00	12 1/2"	4.18	2.35	2.10	1,250	450	400	2, 6, 10		●	SR621SW	3
JS50	12 1/2"	4.18	2.35	2.10	1,250	450	400	4, 6, 8		●	SR621SW	3
JS55	12 1/2"	4.18	2.35	2.10	1,250	450	400	7, 9, 11		●	SR621SW	3

<b>Solar Quartz</b>													
Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)	M (μ)	S (μ)	Subdial position	Day/Date/Month	Power Engine	Running time (month)		
2070	13 2/5"	5.98	1.30	1.90	1,000	500	400			●	4		
2170	16"	5.98	1.30	1.90	1,000	500	400			●	4		
<b>Standard Automatic</b>													
Caliber	Size	Mov't height (mm)	Stem height (mm)	Pinion height (mm)	H (μ)	M (μ)	S (μ)	Subdial position	Day/Date/Month	Parashock	Frequency (vph)	Duration time (hour)	
Long Power Reserve													
8315	11 1/2"	5.67	2.52	1.85	1,130	370	350		Date	●	21,600	60	
Standard	8215	11 1/2"	5.67	2.52	1.85	1,130	370	350	Date	●	21,600	42	
	8205	11 1/2"	5.67	2.52	1.85	1,130	370	350	Day Date	●	21,600	42	
Small Hands	8217	11 1/2"	5.67	2.52	2.35	1,250	650	450	Date	●	21,600	42	
Open-Heart	82S0	11 1/2"	5.67	2.52	1.85	1,130	370	350		●	21,600	42	
	82S5	11 1/2"	5.67	2.52	1.85	1,250	600		5	●	21,600	42	
	82S7	11 1/2"	5.67	2.52	1.85	1,250	600		5, 9	●	21,600	42	
Skeleton	8N24	11 1/2"	5.55	2.00	1.85	1,100	400	350		●	21,600	42	
	8N40	11 1/2"	5.55	2.00	2.37	1,770	600			●	21,600	42	
Small Automatic													
Standard	6T15	8 3/4"	5.98	2.80	1.75	1,050	350	350		●	28,800	40	
	6T51	8 3/4"	5.98	2.80	1.75	1,050	350	350	Day Date	●	28,800	40	
Open-Heart	6T28	8 3/4"	5.23	2.05	1.75	990	410	350		●	28,800	40	
Premium Automatic													
	9039	11 1/2"	3.90	1.53	1.75	900	400	450		●	28,800	42	
	9019	11 1/2"	3.90	1.53	1.75	900	400	450	Date	●	28,800	42	
	9015	11 1/2"	3.90	1.53	2.10	1,200	450	450	Date	●	28,800	42	
Open-Heart	9029	11 1/2"	3.90	1.53	1.35	900	450			●	28,800	42	
	90S5	11 1/2"	3.90	1.53	2.10	1,200	450	450		●	28,800	42	
Complication	9100	13 1/2"	5.52	2.95	2.55	1,650	450	450	12, 3, 6, 9	Day Date Month	●	28,800	40
	9120	13 1/2"	5.52	2.95	2.55	1,650	450	450	3, 6, 9	Day Date Month	●	28,800	40
	9122	13 1/2"	5.52	2.95	2.55	1,650	450	450	3, 9	Day Date Month	●	28,800	40
	9132	13 1/2"	5.52	2.95	2.55	1,650	450	450	12, 6	Date	●	28,800	40
	9133	13 1/2"	5.52	2.95	2.55	1,650	450	450	9	Date	●	28,800	40